

TOSHIBA

Leading Innovation >>>



PRODUCT
OVERVIEW



Strata CIX670 / Strata CIX1200

Sophisticated Business Communications Made Easy

Toshiba's Strata® CIX™670 and Strata CIX1200 IP telephone systems unify, coordinate, and streamline your organization's communications. Support up to 560 phones with CIX670 or 1,000 telephones with CIX1200—even more by networking multiple systems. Easily connect between your main office, branch offices and remote locations to support new levels of collaboration and customer satisfaction.

Strata CIX systems support hundreds of calling features, voice mail and email integration, multimedia collaboration,

unified communications, mobility options and more. Employees can stay connected and productive wherever they are, even using their smartphones as system extensions. You can network up to 128 Strata CIX systems to dramatically expand capacity or seamlessly connect locations.

All Toshiba Strata CIX systems support IP, digital and analog endpoints, making the system ideal for organizations that want to extend the value of existing digital phones while migrating to IP in stages.

SPECIFICATIONS

| Model | Strata CIX670 | | | | Strata CIX1200 | | | |
|---|--|--------------------|--------------------|------------------|--|--------------------|--------------------|--------------------|
| Capacities | 264 trunks or 560 endpoints and combinations up to 672 total. | | | | 440 trunks or 1,000 end points and combinations up to 1,152 total. | | | |
| Rack-mount Chassis | Base Cabinet | | | | Expansion Cabinet (CIX670 max. 6, CIX1200 max. 11) | | | |
| Measurements <i>Metric</i> <i>English</i> | Width | Height | Depth | Weight | Width | Height | Depth | Weight |
| | 483 mm 19 in. | 267 mm 10.5 in. | 358 mm 14 in. | 10 kg 22 lbs. | 483 mm 19 in. | 267 mm 10.5 in. | 358 mm 14 in. | 10 kg 22 lbs. |
| Wall/floor-mount Chassis | Base Cabinet | | | | Expansion Cabinet (CIX670 max. 6, CIX1200 max. 11) | | | |
| Measurements <i>Metric</i> <i>English</i> | Width | Height | Depth | Weight | Width | Height | Depth | Weight |
| | 673 mm 26.5 in. | 295 mm 11.6 in. | 262 mm 10.3 in. | 14 kg 31 lbs. | 673 mm 26.5 in. | 249 mm 9.8 in. | 262 mm 10.3 in. | 13.1 kg 29 lbs. |
| Power Supply Unit (PSU) | Initially Built-in (one per cabinet). | | | | | | | |
| Primary AC Power | Input AC 120VAC, 208VAC, or 240VAC, 4.0 amps maximum. AC Frequency Single-phase (48Hz - 62Hz). 180 watts per cabinet (maximum). | | | | | | | |
| Power Backup | Two or four 12VDC external batteries (80 ampere-hours max.) with built-in charger can provide power backup operation for 2 - 24 hours depending upon configuration (batteries optional). | | | | | | | |
| Chassis Installation | 19" Rack-mount, Wall-mount, or Floor-mount. | | | | | | | |
| Compliance | Safety: UL EMC: FCC Part 15 Class A (Subpart A) HAC and Volume Control: FCC Part 68 Network safety: TIA-968-2-A | | | | | | | |
| FCC Registration | PBX: CJ6MUL-35934-PF-E Hybrid: CJ6MUL-35933-MF-E Key: CJ6MUL-35932-KF-E | | | | | | | |
| Operating Temperature | 32~104° F (0~40° C) | | | | | | | |
| Operating Humidity | 20~80% Relative humidity without condensation | | | | | | | |

SPECIFICATIONS

| | |
|--|---|
| Storage Temperature | -4~140° F (-20~60° C) |
| Voice Mail Compatibility | IPedge® Application Server, Strata® Media Application Server, Strategy® ES, LVMU1A. |
| Trunk Compatibility | Analog: Loop or ground start, DID, E&M; Digital: T1, ISDN PRI; IP: Strata Net IP Networking, SIP Trunking E911: ISDN PRI |
| IP Telephone Compatibility | <p>Toshiba IP5000-Series MEGACO+ models:</p> <ul style="list-style-type: none"> ■ IP5022-SD full-duplex speakerphone with 10 programmable buttons, 4-line x 24-character LCD, and Gigabit Ethernet switch for PC connection. ■ IP5122-SD full-duplex speakerphone with 10 programmable buttons, 4-line x 24-character Backlit LCD with contrast adjustment, and Gigabit Ethernet switch for PC connection. ■ IP5122-SDC full-duplex speakerphone with 10 programmable buttons, 4-line x 24-character Backlit LCD with contrast adjustment, analog CO line interface, and Gigabit Ethernet switch for PC connection. ■ IP5132-SD full-duplex speakerphone with 20 programmable buttons, 4-line x 24-character Backlit LCD with contrast adjustment, and Gigabit Ethernet switch for PC connection. ■ IP5131-SDL full-duplex speakerphone with 20 programmable buttons and LCD key labels, 4-line x 24-character Backlit LCD with contrast adjustment, and Gigabit Ethernet switch for PC connection. <p>802.3af Power-over-Ethernet compliant. 802.1Q Virtual Local Area Network (VLAN) compliant.</p> <ul style="list-style-type: none"> ■ IP5522-SD full-duplex speakerphone with 10 programmable buttons, 4-line x 24-character LCD, and 10/100 Ethernet switch for PC connection. ■ IP5531-SDL full-duplex speakerphone with 20 programmable buttons and LCD key labels, 4-line x 24-character LCD, and 10/100 Ethernet switch for PC connection. ■ IP5622-SD full-duplex speakerphone with 10 programmable buttons, 4-line x 24-character Backlit LCD with contrast adjustment, and 10/100 Ethernet switch for PC connection. ■ IP5631-SDL full-duplex speakerphone with 20 programmable buttons and LCD key labels, 4-line x 24-character Backlit LCD with contrast adjustment, and 10/100 Ethernet switch for PC connection. |
| Digital Telephone Compatibility | <p>Toshiba DP5000-Series models:</p> <ul style="list-style-type: none"> ■ DP5008 single-line telephone with one programmable button. ■ DP5018-S speakerphone with 10 programmable buttons. ■ DP5022-SD speakerphone with 10 programmable buttons and 4-line x 24-character LCD with contrast adjustment. ■ DP5122-SD speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment. ■ DP5032-SD speakerphone with 20 programmable buttons and 4-line x 24-character LCD with contrast adjustment. ■ DP5132-SD speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD with contrast adjustment. ■ DP5130-SDL speakerphone with 20 programmable LCD-label buttons and 4-line x 24-character Backlit LCD with contrast adjustment. |
| Analog Device Compatibility | Dealer-supplied standard telephones with or without Caller ID, FAX machines, modems, etc. |
| Answer Position Options | LM5110 Add-On Module with 10 programmable Backlit LCD-label buttons. KM5020 Add-On Module with 20 programmable buttons. IDM5060 and DDM5060 DSS/BLF Console with 60 programmable buttons. Strata PC Attendant Console. |
| User Mobility Options | IPMobility app to use Apple® iOS and Android™ smartphones as system extensions. Call Manager® Advanced and Call Manager Standard support for PCs and laptops with the IPedge® Application Server or Strata ACD. Wireless IP telephone support via Wi-Fi® Wireless LAN. Cordless digital telephone. IP4100 Wireless SIP DECT Telephone. |
| System Administration | Network eManager® centralized installation/maintenance of all Strata CIX systems for technicians and administrators. eMonitor monitoring of alarm conditions from multiple Strata CIX systems. My Phone Manager® personal administration for individual users. Traffic measurement reports stored on local SD flash memory card. |
| Standard System Features | Over 300 standard telephony features to provide the functionality you need. |
| Advanced Application Options | Voice Mail/Auto Attendant, Unified Messaging, Fax Integration, Automated Speech Recognition, Text-To-Speech, Interactive Voice Response, Automatic Call Distribution and Reporting, Voice Over Internet Protocol, Strata Net multiple system networking, FeatureFlex™ adaptability/customization tools, centralized network SMDR, and more. |
| Multi-system Networking | Strata Net networking of up to 128 nodes via IP or ISDN PRI. |
| Feature Customization | FeatureFlex adaptability tools for feature creation/customization. |

TOSHIBA
Leading Innovation >>>



Toshiba America Information Systems, Inc.
Telecommunication Systems Division

9740 Irvine Blvd., Irvine, CA 92618-1697
To locate an Authorized Dealer, call: (800) 222-5805
National Accounts (800) 234-4873
www.telecom.toshiba.com

© 2013 Toshiba America Information Systems, Inc. All product, service and company names are trademarks, registered trademarks or service marks of their respective owners. Information including without limitation specifications, availability, content of services, and contact information is subject to change without notice.

Literature Order #:TSD-CIX-BR-670-DS-VL/4500139